

Modal operator

From Wikipedia, the free encyclopedia

Revision as of 19:16, 2 June 2006; Filemon (Talk | contribs)

(diff) ← Older revision | Current revision | Newer revision → (diff)

A **modal operator** is a logical connective, in the language of a modal logic, which forms propositions from propositions. In general, a modal operator is *formally* characterised by being non-truth-functional, and *intuitively* characterised by expressing a modal attitude (such as necessity, possibility, belief, or knowledge) towards the proposition which it is applied to.

Examples

- In the alethic modal logic of C.I. Lewis, the modal operator \Box expresses necessity: if the proposition A is read as "it is true that A holds", the proposition $\Box A$ is read as "it is *necessarily* true that A holds".
- In the tense logic (more commonly now called temporal logic) of A.N. Prior, the proposition A is read as " A is true at the present time"; $F A$, as " A will be true at some time in the future"; and $G A$, as " A is true now and will always be true".
- The previous two examples are of unary or monadic modal operators. As an example of a dyadic modal operator -- which produces a new proposition from *two* old propositions -- is the operator P in the dyadic deontic logic of G.H. von Wright. $P(A,B)$ expresses that " A is obligatory under the circumstances B ".

Retrieved from "http://en.wikipedia.org/wiki/Modal_operator"

Categories: Mathematical logic stubs | Modal logic

-
- This version of the page has been revised.
Besides normal editing, the reason for revision may have been that this version contains factual inaccuracies, vandalism, or material not compatible with the GFDL.